

## Kennedy 125x3x22.23mm A24RBF FLAT CUTTING DISC



Type 41 Flat Reinforced Cutting For use with all portable angle grinders. 180mm to 230mm discs can also be used on circular saws, and 300 to 350mm discs are for use with chop saws/cut-off machines, subject to bore compatibility. Not to be used for wet cutting. Grade A24/A36 - For general-purpose cutting on metals. Grade C24 - For general-purpose cutting on stone. Depressed Centre & Flat Reinforced Cutting & Grinding Discs All Kennedy Depressed Centre and Flat Reinforced Cutting Wheels now carry the OSA (The Organisation for the Safety of Abrasives) mark of approval. OSA is an association of the world's leading abrasives manufacturers. In France, it is mandatory to use only OSA-certified rough grinding wheels and cutting wheels. Similarly in Germany and Italy, it is strongly recommended that abrasive products conform to the relevant EN standards. OSA marked products are guaranteed to meet or exceed the highest worldwide safety standards, including those of the Comite Europeen de Normalisation (CEN), the European standards body that issues EN standards, and of ANSI in the USA.

Specifications	Details
Grain Size	24-Coarse
Maximum RPM	12200
Optimum Angle For Use	90 Å°
Product Number	1120015
Abrasive Material	Aluminium Oxide
Special Features	Good Performance Competitively Priced
Disc Diameter	125 mm
Bond Type	Resin Bonded with Fibre Reinforcment
Bore	22
Hardness	Hard

Specifications	Details
Additional Conformity	Complies to oSa Regulations Manufactured According to EN12413
Thickness	3 mm
Series	General Purpose
For Use On	Non Ferrous Metal
Grade Designation	A24R-BF
Cutting Application	Cast Construction Steel alloyed & unalloyed General Purpose use on Steel Steel Cable Steel Profiles Tank Construction & Fabrication
SKU	KEN2306950GTSK
Type	Type 41
Weight	1
Brand	Kennedy

