

## Chicago Pneumatic CP7782-SP6 Impact Wrenches - #5 Spline 500-2000NM



High Torque & Comfort. High efficiency motor, yet economical with durable reinforced clutch mechanism. Durable impact wrench with great power for the toughest jobs on heavy vehicles. Range: 500 - 2000 Nm 370 - 1475 ft.lbs

Specifications	Details
Free Speed	5200 rpm
Blows per Minute	Metric: M32 mm Imperial: 500
Actual air consumption	Metric: 19.2 l/s Imperial: 40.7 cfm
Sound pressure	100 db(A)
Sound Power	111 db(A)
Air inlet thread size	1/2"
Power/weight ratio	Metric: 257.4 Nm/kg Imperial: 86.5 ft.lb/lb
Maximum Torque (reverse)	Metric: 2600 Nm Imperial: 1620 ft.lbs
Range Metric	500 - 2000 Nm
Over carton	Metric: 670*245*130 mm Imperial: 26.35*9.6*5.11
Range Imperial	370 - 1475 ft.lbs
Min. Hose Size	Metric: 13 mm Imperial: 1/2"
Product Number	8941077821
Brand	Chicago Pneumatic
Sound uncertainty	3 db(A)
Average air consumption	Metric: 4.8 l/s Imperial: 10 cfm
Model Number	CP7782-SP6
Square Drive	#5 spline
Length	Metric: 370 mm Imperial: 14.7"

Specifications	Details
Vibration uncertainty (K)	1.8 m/s <sup>2</sup>
Vibration	7.8 m/s <sup>2</sup>
Bolt Size	Metric: M32 mm
Net weight	Metric: 11.6 kg Imperial: 25.55 lb
Vibration ISO	ISO-28927-2

