



Chicago Pneumatic CP2037 Screwdrivers - Impact (Double Rocking Dog) 18-28NM

Compact & high torque. Powerful torque & lightweight. Quick torque adjustment. Perfect for fast self-drilling applications. Range: 18 - 28 Nm 13.3 - 20.7 ft.lbs

Specifications	Details
Screw type hard	x
Bit holder	Quick Change Hexagonal Female
Screw type very soft	x
Vibration uncertainty (K)	- m/s ²
Vibration ISO	ISO-28927-2
Vibration	<2.5 m/s ²
Screw type soft	x <input type="checkbox"/>
Air inlet thread size	1/4"
Sound pressure	88 db(A)
Clutch type	Impact (Double Rocking Dog)
Min working torque	Metric: 18 Nm Imperial: 13.3 ft.lbs
Sound Power	99 db(A)
Actual air consumption	Metric: 6.1 l/s 366 l/mn Imperial: 13 cfm
Average air consumption	13 cfm
Output drive	1/4"
Max working torque	Metric: 28 Nm Imperial: 20.7 ft.lbs
Product Number	6151922037
Handle Type	Straight
Net weight	Metric: 0.82 kg Imperial: 1.81 lb

Specifications	Details
Free speed air consumption	Metric: 6.1 l/s Imperial: 13 cfm
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Brand	Chicago Pneumatic
Length	Metric: 207 mm Imperial: 8.15"

