

Chicago Pneumatic CP2136 Screwdrivers - Impact (Double Rocking Dog) 8-21NM



Compact, fast & easy to use. Compact & Lightweight. Low air consumption for a better efficiency. Excellent for various MRO applications Range: 8 - 21 Nm 5.93 - 15.5 ft.lbs

Specifications	Details
Screw type soft	X
Max working torque	Metric:21 Nm Imperial: 15.5 ft.lbs
Screw type very soft	X
Screw type hard	X
Bit holder	Quick Change Hexagonal Female
Over carton	Metric: 400*258*291 mm Imperial: 15.75*10.16*11.46
Bolt Size	M4-M6 mm
Net weight	Metric: 0.68 kg Imperial: 1.49779735682819 lb
Output drive	1/4"
Actual air consumption	Metric: 3.2 l/s Imperial: 6.78 cfm
Sound pressure	89 db(A)
Clutch type	Impact (Double Rocking Dog)
Min working torque	Metric: 8 Nm Imperial: 5.93 ft.lbs
Model Number	CP2136
Free speed air consumption	Metric: 4.16 l/s Imperial: 8.81 cfm
Sound Power	100 db(A)

Specifications	Details
Air inlet thread size	1/4"
Handle Type	Straight
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Diameter	Metric: 20 mm Imperial: 0.785"
Product Number	8941021360
Brand	Chicago Pneumatic
Length	Metric: 185 mm Imperial: 7.28346456692913"
Vibration	7.4 m/s ²
Vibration ISO	ISO-28927-2
Vibration uncertainty (K)	2.8 m/s ²
Height	Metric: 50 mm Imperial: 1.96850393700787"

