



Chicago Pneumatic CP2141 Screwdrivers - Impact (Double Rocking Dog) 10-24NM

Compact, fast & easy to use. Compact & Lightweight. Low noise level for operator comfort. Excellent for various MRO applications. Range: 10 - 24 Nm 7.38 - 17.7 ft.lbs

Specifications	Details
Screw type soft	x
Screw type hard	x
Max working torque	Metric: 24 Nm Imperial: 17.7 ft.lbs
Net weight	Metric: 0.87 kg Imperial: 1.91629955947137 lb
Bit holder	Hexagonal Female
Free Speed	13000 rpm
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Handle Type	Pistol
Diameter	Metric: 21 mm Imperial: 0.825"
Length	Metric: 143 mm Imperial: 5.62992125984252"
Model Number	CP2141
Output drive	1/4"
Actual air consumption	Metric: 6.23 l/s Imperial: 13.2 cfm
Sound pressure	77 db(A)
Clutch type	Impact (Double Rocking Dog)
Min working torque	Metric: 10 Nm Imperial: 7.38 ft.lbs

Specifications	Details
Height	Metric: 150 mm Imperial: 5.90551181102362"
Sound Power	88 db(A)
Air inlet thread size	1/4"
Brand	Chicago Pneumatic
Product Number	8941021410
Vibration	5.3 m/s ²
Vibration ISO	ISO-28927-2
Vibration uncertainty (K)	2.1 m/s ²
Screw type very soft	x
Over carton	Metric: 412*367*212 mm Imperial: 16.22*14.45*8.35
Bolt Size	M4-M6 mm
Free speed air consumption	Metric: 8.53 l/s Imperial: 18.07 cfm

