



## Chicago Pneumatic CP7225CVE Orbital sanders

Powerful & comfortable. Operator comfort with ergonomic palm shape. Productivity increased with low vibrations level. Powerful and ergonomic palm shape for vertical and horizontal applications. 3/32 (2.5 mm): used for final sanding, finishing, and pre-polishing processes

Specifications	Details
Min. Hose Size	Metric: 10 mm Imperial: 3/8"
Free Speed	12000 rpm
Pad type	H&L
Sound Power	92 db(A)
Sound pressure	81 db(A)
Actual air consumption	Metric: 7.6 l/s 453 l/mn Imperial: 16 cfm
Model Number	CP7225CVE
Average air consumption	Metric: 3.8 l/s 227 l/mn Imperial: 8 cfm
Spindle thread	5/16-24
Power	Metric: 210 W Imperial: 0.3 hp
Net weight	Metric: 0.83 kg Imperial: 1.83 lb
Free speed air consumption	Metric: 8 l/s Imperial: 18 cfm
Air inlet thread size	1/4"
Paper size	Metric: 150 mm Imperial: 6"
Pad diameter	Metric: 150 mm Imperial: 6"
Vibration uncertainty (K)	2.08 m/s <sup>2</sup>
Vibration	3.7 m/s <sup>2</sup>
Vibration ISO	ISO-28927-3

Specifications	Details
Length	Metric: 221*150*105 mm Imperial: 8.7*6*4.1
Brand	Chicago Pneumatic
Product Number	8941272253
Pad holes number	6
Pad type Hook & Loop	yes
Pad type PSA	no
Vacuum	Central vacuum
Height over spindle	Metric: 105 mm Imperial: 4.1"
Orbit diameter	Metric: 2 1/2 mm Imperial: 3/32"
Central vacuum	x

