

UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538



Kern WTB-3N 10Kg Bench Scale

Recessed grips on the underside of the scale for easy transportationHigh mobility its rechargeable batteries (optional) and low weightCompact size, practical for small spaces

| Specifications | Details |
|---|----------------------------------|
| Weighing range [Max] | 15 kg |
| Material weighing plate: | stainless steel |
| Dimensions housing (WxDxH): | 285 mm x 315 mm x 128 mm |
| Minimum humidity | 0 % |
| Tare range: | -14998000 mg |
| Weighing with tolerance range: | yes |
| Capacity display: | yes |
| Resolution | 7500 |
| Product Number | WTB 10Kg-3N |
| Brand | Kern |
| Model Number | WTB-3N |
| Net weight | 3.1 kgs |
| Casing material: | Plastic |
| Dimensions of weighing plate (WÃ \Box DÃ \Box H): | 260 mm x 200 mm x 16,2 mm |
| Weighing surface (WxD): | 260 mm x 200 mm |
| Rechargeable battery: | Rchrg. battery optional - intern |
| Display digit height: | 25 mm |



UAE Email: mathews@generaltechuae.com Tel : +971 (0) 2 550 7702 Fax : +971 (0) 2 550 7706

SAUDI Mathews@generaltechsaudi.com Tel : +966 (0) 3 834 4264 Fax : +966 3 834 4538

| Specifications | Details |
|---------------------------------------|--------------------------|
| Charging time | 12 h |
| Input voltage | 110 V - 230 V AC |
| Operating time (Backlight off) | 50 h |
| Adjustment options | External calibration |
| Operating time (Backlight on): | 30 h |
| Linearity | 4 g |
| Mains adapter/adapter included: | CH EURO UK US |
| Revolving screw feet: | yes |
| Additional Display possible: | yes |
| Overall dimensions mounted (WÃ]DÃ]H): | 285 mm x 315 mm x 128 mm |
| Level indicator: | yes |
| Gross weight | 4 kgs |
| Minimum ambient temperature | -10 °C |
| Maximum operating temperature | 40 °C |
| Maximum humidity | 80 % |
| Weighing units | kg |
| Weighing system | Strain gauge |
| Warm up time | 30 min |
| Stabilisation time | 2 s |
| Reproducibility | 2 g |
| Recommended adjusting weight | 15 kg (M1) |
| Readout [d] | 2 g |