Rodcraft RC9077

Cordless 1/2" Impact Wrench

Optimal to perform your tire-changing activities.

The Rodcraft RC9077 Cordless 1/2" Impact Wrench exceeds expectations in maximum loosening torque, design and performance. Keeping an outstanding maximum loosening torque of over 1500 Nm, it can easily break loose hard-tightened bolts in multiple applications.



Outstanding performance:

- Maximum loosening torque up to 1500 Nm
- 200 tightenings per battery charge



Outstanding ergonomic features & usability

- · Anti-slip handle
- Reverse button next to trigger for easy access
- Integrated LED light for better work area lighting
- · Perfectly balanced

Durability & Rugged

- · Brushless motor
- · Multiple bumpers for tool protection
- Impact clutch mechanism in metal housing

Easy to use

- 3 power settings forward
- 2 power settings in reverse
- · Progressive trigger







For products that are not purchased in a set, the battery, charger and soft bag are not included. More Details see page 2.





© 2024 Rodcraft. Subject to technical adjustments or mistakes. For products that are not purchased in a set, the batten, charger and soft bag are not included-


Technical data


MODEL	RC9077
Item number	8951000465
Output drive size (inch)	1/2"
Torque on tightening (Nm) (3 settings)	286 - 538 - 1100+
Max. loosening torque (Nm)	1500
Speed Range (rpm)	0 to 1700
Impact Rate Range (bpm)	0 to 2200
Rated Voltage (V)	20
Bare Tool Weight* (kg)	3
Tool Weight incl. battery (kg)	3,68
Bare Tool Length (L) (mm)	230
Bare Tool Width (W) (mm)	87
Bare Tool Height (H) (mm)	245
Recommended Charging Temperature (°C)	0 to +45
Storage Temperature (°C)	20 to +50
Operating Temperature (°C)	-20 to +70

Further information such as exploded views and safety data sheet can be found online:




Choose from 3 battery variants: 2Ah, 4Ah and 6Ah. All 3 Batteries (2Ah, 4Ah and 6Ah) are compatible with the 3 Tools.





Technical data charger

RC20CHEU	RC20CHUK
8951000470	8951000471
230-240V / 50Hw 85 W	230-240V / 50Hw 85 W
21.5 VDC, 3.5 A	21.5 VDC, 3.5 A
0.36 Kg (0.49 lbs)	0.36 Kg (0.49 lbs)
Europlug	BS 1363
	8951000470 230-240V / 50Hw 85 W 21.5 VDC, 3.5 A 0.36 Kg (0.49 lbs)



Technical data batteries







MODEL	RC20BA20	RC20BA40	RC20BA60
Item number	8951000467	8951000468	8951000469
Ah	2	4	6
Battery Type	Li-Ion Battery	Li-Ion Battery	Li-Ion Battery
Battery Voltage	20	20	20
Charging Time (mins)	60	75	110
A Width (mm)	78	78	81
B Length (mm)	123	123	130
C Height (mm)	49	69	82
Weight (kg)	0.4	0.68	0.92
Weight (lbs)	0.8	1.5	2.02

Sets, available as a package

	RC9087K4	RC9087K6
Item number	8951000475	8951000477
Model	RC9087	RC9087
Batteries	2 x 4 Ah	2 x 6 Ah
Charger	V	V
Soft bag	✓	✓



The products are packaged in eco-friendly cardboard boxes without chemical treatment, like bleaching.
Use of harmful materials like foam or plastic bags inside the boxes

is minimized.



